

Marlin 50

Combines the convenience of a tabletop model with the capacity of a floor model

Quieter than a floor model

Plug-and-Play

Faster than a tabletop model



Extracting air, adding value





Save up to 25% on energy costs

Compose your ideal Marlin 50

The Henkelman Marlin 50 is a full-fledged floor model with matching capacity but with the convenience of a tabletop model. It simply operates on 1 phase - 230 V so it is a matter of plug-and-play. The pump in this machine only runs when the machine is in a vacuum cycle so you do not experience a constant machine noise in your workspace. This also saves on your energy costs.

The Marlin 50 can be equipped with various options. So you can tailor your machine to suit your specific needs. A number of options can even be added after you have taken the machine into service.

Specs	Marlin 50
Chamber LxBxH (mm)	520 x 500 x 200
Machine LxBxH (mm)	710 x 700 x 1025
Seal bar (mm)	1 x 590 / 2 x 510
Pumpcapacity (m ³ /h)	40
Machinecycle (sec.)	11 - 27
Power (kW)	1,1
Voltage	230V-1-50
Weight (kg)	136
Seal bar configuration standard	
Seal bar configuration optional	

Equipped as standard with

- 10-program memory
- Soft air
- Time control
- Red meat function
- Automatic service message
- 2 insert plates

Optional

- Sensor control
- Liquid control
- Advanced Control System (ACS)
- Gas Flush (MAP)
- 1-2 Cut-off seal

Accessories

- Inclined insert plate
- Thermal label printer
- External adapter
- Maintenance kit floor models



Optionally available with ACS control →



Titaniumlaan 10
5221 CK 's-Hertogenbosch
The Netherlands

+31 73 621 36 71
info@henkelman.com
www.henkelman.com

